

Overview

Each Tube has four adjustable guide rods to enable it to take various size plates for 8"-12" (205mm-305mm) diameter with a maximum capacity of around 65 plates per tube. The dispensers have a Pop-Up variable spring system to accommodate different weights of plates. Lift off top plate and the next one automatically moves up into position Heated units complete with Impact resistant ABS covers and 13amp plug and cable Temperature controlled by internal thermostat with surface level illuminated on/off switch for easy operation.



Key Features:

- Well proven elements and components provide evenly distributed heat.
- Factory set thermostatic controls internal air at 60° C.
- Interior finished in clinical bright polished stainless steel.
- Capacity approximately 65 plates per tube depending on type, profile and thickness.
- Heated units supplied with an ABS lid and 2 metre long cable and 13 amp plug.
- Simplistic easy adjustable springs allows repeated pop up plate presentation.
- 24/7 operation.
- Self-contained unit. Electrics are integral no awkward fitting under counter control boxes.
- Easily adjustable plate guides, no tools required.

Options:

- ABS lid for CPDA1 and CPDA2 models





Model	Type	Weight (kg)	L x D x H (mm)	Height to worktop	Power Rating/ Electrical supply
CPDA1	Neutral	50	558 x 700 x 956	900mm	N/A
CPDA2	Neutral	70	558 x 800 x 956	900mm	N/A
CPDH1	Heated	50	558 x 700 x 956	900mm	0.6kw / 13amp
CPDH2	Heated	70	558 x 800 x 956	900mm	1.20kw / 13amp

Note: CPDA2 and CPDH2 do not fit into a 700mm deep body

