







Moffat Specification

-----1.2mm Thick 304 Grade St/Steel TOP TURNDOWN (Front & Ends - 4 Sides On C/Tables) -----UPSTAND (WB's Only) ---- 50mm High / 21mm Return to Wall / 12mm Downturn UNDERTOP ------- 1.2mm Thick Galvanised Steel UNDERSHELF (If Applicable) -- 1mm Thick 430 Grade St/Steel, 43mm Turndowns - 30x30mm 430 Grade St/Steel Tie Bars (If Applicable)--PANELS (If Applicable) ------ 30x30/15/5mm 430 Grade St/Steel ----- 0.7mm Thick 430 Grade St/Steel FEET (If Applicable) ------ Aluminium Adjustable Floor Fixing +20mm/-15mm CASTORS (If Applicable) --

ALL DIMENSIONS IN (mm), TOLERANCE = LINEAR ± 0.5mm, ANGULAR ± 0.5mm (OR AS STATED). ALL SHARP EDGES TO BE REMOVED FROM SHEET METAL PARTS. ALL SHEET METAL DIMENSIONS ARE I/S (INSIDE SIZES) (UNLESS OTHERWISE STATED)

ALL SHELT HETAL DITIENS	SIGNS THE 1/5 (INSIDE SIZES) (ONLESS OTHERWISE STATED)		,,		, <u></u>			
Product	FABRICATION	Product No	SCT965	may be made, and no a	No reproduction or publication of this drawing may be made, and no article may be manufactured		MOFFAT	
Description	CENTER TABLE 900x650x900mm HIGH			without prior written cons	or assembled in accordance with this drawing without prior written consent. This prohibition is a term of any contract relating to this drawing. Rights reserved			
Material/Finish	Thickness	Desp/Date			under the Copyright Act 1956 as ammended by the Design Copyright Act 1968.		Conpany	
Legacy P/N	Weight	Quote No.	N/A	Dwg No.	CTA-0	00704 Issue		ue
Client	N/A	SO Number	N/A	Drawn By	J.And	lerson		A
Client Project	N/A	Approved By		Date	18/01/2018		A	
E & R MOFFAT LTD, SEABEGS ROAD, BONNYBRIDGE, FK4 2BS, T: +44 (0)1324 812272, E: sales@ermoffat.co.uk, Web: www.ermoffat.co.uk				Scale	1:20	Sheet	1/1	A4