



**Moffat Specification**

- TOP ----- 1.2mm Thick 304 Grade St/Steel
- TOP TURNDOWN (Front & Ends) ----- 50mm High / 21mm Return to Wall / 12mm Downturn
- UPSTAND ----- 50mm High / 21mm Return to Wall / 12mm Downturn
- BOWL ----- 1.2mm Thick 304 Grade St/Steel
- BOWL FITTINGS ---- 38mm Waste With Corner Strainer or Overflow Plug & Chain
- TAP HOLES PER BOWL ----- 2x Ø25mm AT 180mm Centres
- RELIEF PATTERN DRAINER WITH ANTI-DRIP EDGE ----- Wipe Dry
- UNDERSHELF ----- 1mm Thick 430 Grade St/Steel, 43mm Turndowns
- LEGS ----- 30x30mm 430 Grade St/Steel
- Tie Bars (If Applicable)----- 30x30/15/5mm 430 Grade St/Steel
- PANELS (If Applicable) ----- 0.7mm Thick 430 Grade St/Steel
- FEET ----- Aluminium Adjustable Floor Fixing +20mm/-15mm  
c/w Earth Bonding Tab

ALL SHEET METAL DIMENSIONS ARE I/S (INSIDE SIZES) (UNLESS OTHERWISE STATED)

ALL DIMENSIONS IN (mm), TOLERANCE = LINEAR ± 0.5mm, ANGULAR ± 0.5mm (OR AS STATED). ALL SHARP EDGES TO BE REMOVED FROM SHEET METAL PARTS.

Product	FABRICATION			Product No	SSU1265BD			 The Catering Equipment Company				
Description	SINK UNIT 1200x650x900mm High			Desp/Date								
Material/Finish	Thickness			Quote No.	N/A			Dwg No.	SUA-001358	Issue		
Legacy P/N	Weight			SO Number	N/A			Drawn By	J.Anderson	<b>A</b>		
Client	N/A			Approved By				Date	31/01/2018			
Client Project	N/A							Scale	1 : 20	Sheet	1 / 1	<b>A4</b>