



**Moffat Specification**

- TOP -----1.2mm Thick 304 Grade St/Steel
- TOP TURNDOWN (Front & Ends) ----- 50mm
- UPSTAND ----- 50mm High / 21mm Return to Wall / 12mm Downturn
- BOWL -----1.2mm Thick 304 Grade St/Steel
- BOWL FITTINGS ---- 38mm Waste With Corner Strainer or Overflow Plug & Chain
- TAP HOLES PER BOWL ----- 2x Ø25mm AT 180mm Centres
- RELIEF PATTERN DRAINER WITH ANTI-DRIP EDGE ----- Wipe Dry
- UNDERSHELF ----- 1mm Thick 430 Grade St/Steel, 43mm Turndowns
- LEGS ----- 30x30mm 430 Grade St/Steel
- Tie Bars (If Applicable)----- 30x30/15/5mm 430 Grade St/Steel
- PANELS (If Applicable) ----- 0.7mm Thick 430 Grade St/Steel
- FEET ----- Aluminium Adjustable Floor Fixing +20mm/-15mm  
c/w Earth Bonding Tab

ALL SHEET METAL DIMENSIONS ARE I/S (INSIDE SIZES) (UNLESS OTHERWISE STATED)

ALL DIMENSIONS IN (mm), TOLERANCE = LINEAR ± 0.5mm, ANGULAR ± 0.5mm (OR AS STATED). ALL SHARP EDGES TO BE REMOVED FROM SHEET METAL PARTS.

Product	FABRICATION			Product No	SSU1265DB			© No reproduction or publication of this drawing may be made, and no article may be manufactured or assembled in accordance with this drawing without prior written consent. This prohibition is a term of any contract relating to this drawing. Rights reserved under the Copyright Act 1956 as amended by the Design Copyright Act 1968.		
Description	SINK UNIT 1200x650x900mm High			Desp/Date						
Material/Finish		Thickness		Quote No.	N/A			Dwg No.	SUA-001361	Issue
Legacy P/N		Weight		SO Number	N/A			Drawn By	J.Anderson	<b>A</b>
Client	N/A			Approved By				Date	31/01/2018	
Client Project	N/A			Scale	1 : 20			Sheet	1 / 1	<b>A4</b>
E & R MOFFAT LTD, SEABEGS ROAD, BONNYBRIDGE, FK4 2BS, T: +44 (0)1324 812272, E: sales@ermoffat.co.uk, Web: www.ermoffat.co.uk										