



**Moffat Specification**

TOP ----- 1.2mm Thick 304 Grade St/Steel  
 TOP TURNDOWN (Front & Ends) ----- 50mm  
 UPSTAND ----- 50mm High / 21mm Return to Wall / 12mm Downturn  
 BOWL ----- 1.2mm Thick 304 Grade St/Steel  
 BOWL FITTINGS ----- 38mm Waste With Corner Strainer or Overflow Plug & Chain  
 TAP HOLES PER BOWL ----- 2x Ø25mm AT 180mm Centres  
 RELIEF PATTERN DRAINER WITH ANTI-DRIP EDGE ----- Wipe Dry  
 UNDERSHELF ----- 1mm Thick 430 Grade St/Steel, 43mm Turndowns  
 LEGS ----- 30x30mm 430 Grade St/Steel  
 Tie Bars (If Applicable) ----- 30x30/15/5mm 430 Grade St/Steel  
 PANELS (If Applicable) ----- 0.7mm Thick 430 Grade St/Steel  
 FEET ----- Aluminium Adjustable Floor Fixing +20mm/-15mm  
 c/w Earth Bonding Tab

ALL SHEET METAL DIMENSIONS ARE I/S (INSIDE SIZES) (UNLESS OTHERWISE STATED)

ALL DIMENSIONS IN (mm), TOLERANCE = LINEAR ± 0.5mm, ANGULAR ± 0.5mm (OR AS STATED). ALL SHARP EDGES TO BE REMOVED FROM SHEET METAL PARTS.

Product	FABRICATION			Product No	SSU127BD			© No reproduction or publication of this drawing may be made, and no article may be manufactured or assembled in accordance with this drawing without prior written consent. This prohibition is a term of any contract relating to this drawing. Rights reserved under the Copyright Act 1956 as amended by the Design Copyright Act 1968.			
Description	SINK UNIT 1200x700x900mm High			Desp/Date							
Material/Finish	Thickness			Quote No.	N/A			Dwg No.	SUA-001410		Issue
Legacy P/N	Weight			SO Number	N/A			Drawn By	J.Anderson		<b>A</b>
Client	N/A			Approved By				Date	01/02/2018		
Client Project	N/A			Scale	1 : 20		Sheet	1 / 1		<b>A4</b>	