



Moffat Specification

- TOP -----1.2mm Thick 304 Grade St/Steel
- TOP TURNDOWN (Front & Ends) ----- 50mm High / 21mm Return to Wall / 12mm Downturn
- UPSTAND -----1.2mm Thick 304 Grade St/Steel
- BOWL ----- 38mm Waste With Corner Strainer or Overflow Plug & Chain
- BOWL FITTINGS ----- 2x Ø25mm AT 180mm Centres
- TAP HOLES PER BOWL ----- Wipe Dry
- RELIEF PATTERN DRAINER WITH ANTI-DRIP EDGE ----- 1mm Thick 430 Grade St/Steel, 43mm Turndowns
- UNDERSHELF ----- 30x30mm 430 Grade St/Steel
- LEGS ----- 30x30/15/5mm 430 Grade St/Steel
- Tie Bars (If Applicable) ----- 0.7mm Thick 430 Grade St/Steel
- PANELS (If Applicable) ----- Aluminium Adjustable Floor Fixing +20mm/-15mm
- FEET ----- c/w Earth Bonding Tab

ALL SHEET METAL DIMENSIONS ARE I/S (INSIDE SIZES) (UNLESS OTHERWISE STATED)

ALL DIMENSIONS IN (mm), TOLERANCE = LINEAR ± 0.5mm, ANGULAR ± 0.5mm (OR AS STATED). ALL SHARP EDGES TO BE REMOVED FROM SHEET METAL PARTS.

Product	FABRICATION			Product No	SSU1565BBD			
Description	SINK UNIT 1500x650x900mm High							
Material/Finish	Thickness			Desp/Date			<small>© No reproduction or publication of this drawing may be made, and no article may be manufactured or assembled in accordance with this drawing without prior written consent. This prohibition is a term of any contract relating to this drawing. Rights reserved under the Copyright Act 1956 as amended by the Design Copyright Act 1968.</small>	
Legacy P/N	Weight			Quote No.	N/A	Dwg No.		SUA-001384
Client	N/A			SO Number	N/A		Issue	
Client Project	N/A			Approved By		Date	31/01/2018	
E & R MOFFAT LTD, SEABEGS ROAD, BONNYBRIDGE, FK4 2BS, T: +44 (0)1324 812272, E: sales@ermoffat.co.uk, Web: www.ermoffat.co.uk							Scale	1 : 20
							Sheet	1 / 1
								A4

