



Moffat Specification

TOP	-----1.2mm Thick 304 Grade St/Steel
TOP TURNDOWN (Front & Ends)	----- 50mm
UPSTAND	----- 50mm High / 21mm Return to Wall / 12mm Downturn
BOWL	-----1.2mm Thick 304 Grade St/Steel
BOWL FITTINGS	---- 38mm Waste With Corner Strainer or Overflow Plug & Chain
TAP HOLES PER BOWL	----- 2x Ø25mm AT 180mm Centres
RELIEF PATTERN DRAINER WITH ANTI-DRIP EDGE	----- Wipe Dry
UNDERSHELF	----- 1mm Thick 430 Grade St/Steel, 43mm Turndowns
LEGS	----- 30x30mm 430 Grade St/Steel
Tie Bars (If Applicable)	----- 30x30/15/5mm 430 Grade St/Steel
PANELS (If Applicable)	----- 0.7mm Thick 430 Grade St/Steel
FEET	----- Aluminium Adjustable Floor Fixing +20mm/-15mm c/w Earth Bonding Tab

ALL SHEET METAL DIMENSIONS ARE I/S (INSIDE SIZES) (UNLESS OTHERWISE STATED)

ALL DIMENSIONS IN (mm), TOLERANCE = LINEAR ± 0.5mm, ANGULAR ± 0.5mm (OR AS STATED). ALL SHARP EDGES TO BE REMOVED FROM SHEET METAL PARTS.

Product	FABRICATION			Product No	SSU157BBD			 The Catering Equipment Company		
Description	SINK UNIT 1500x700x900mm High			Desp/Date						
Material/Finish	Thickness			Quote No.	N/A			Dwg No.	SUA-001431	Issue
Legacy P/N	Weight			SO Number	N/A			Drawn By	J.Anderson	A
Client	N/A			Approved By				Date	01/02/2018	
Client Project	N/A			Scale	1 : 20			Sheet	1 / 1	A4
E & R MOFFAT LTD, SEABEGS ROAD, BONNYBRIDGE, FK4 2BS, T: +44 (0)1324 812272, E: sales@ermoffat.co.uk, Web: www.ermoffat.co.uk										

© No reproduction or publication of this drawing may be made, and no article may be manufactured or assembled in accordance with this drawing without prior written consent. This prohibition is a term of any contract relating to this drawing. Rights reserved under the Copyright Act 1956 as amended by the Design Copyright Act 1968.