



- Moffat Specification**
- TOP -----1.2mm Thick 304 Grade St/Steel
  - TOP TURNDOWN (Front & Ends) ----- 50mm
  - UPSTAND ----- 50mm High / 21mm Return to Wall / 12mm Downturn
  - BOWL -----1.2mm Thick 304 Grade St/Steel
  - BOWL FITTINGS ----- 38mm Waste With Corner Strainer or Overflow Plug & Chain
  - TAP HOLES PER BOWL ----- 2x Ø25mm AT 180mm Centres
  - RELIEF PATTERN DRAINER WITH ANTI-DRIP EDGE ----- Wipe Dry
  - UNDERSHELF ----- 1mm Thick 430 Grade St/Steel, 43mm Turndowns
  - LEGS ----- 30x30mm 430 Grade St/Steel
  - Tie Bars (If Applicable)----- 30x30/15/5mm 430 Grade St/Steel
  - PANELS (If Applicable) ----- 0.7mm Thick 430 Grade St/Steel
  - FEET ----- Aluminium Adjustable Floor Fixing +20mm/-15mm  
c/w Earth Bonding Tab

ALL SHEET METAL DIMENSIONS ARE I/S (INSIDE SIZES) (UNLESS OTHERWISE STATED) ALL DIMENSIONS IN (mm), TOLERANCE = LINEAR ± 0.5mm, ANGULAR ± 0.5mm (OR AS STATED). ALL SHARP EDGES TO BE REMOVED FROM SHEET METAL PARTS.

Product	FABRICATION	Product No	SSU187BBD			© No reproduction or publication of this drawing may be made, and no article may be manufactured or assembled in accordance with this drawing without prior written consent. This prohibition is a term of any contract relating to this drawing. Rights reserved under the Copyright Act 1956 as amended by the Design Copyright Act 1968.	The Catering Equipment Company	
Description	SINK UNIT 1800x700x900mm High		Desp/Date					
Material/Finish	Thickness	Weight	Quote No.	N/A		Dwg No.	SUA-001441	
Legacy P/N			SO Number	N/A		Drawn By	J.Anderson	
Client	N/A		Approved By			Date	01/02/2018	
Client Project	N/A				Scale	1 : 20	Sheet	1 / 1
E & R MOFFAT LTD, SEABEGS ROAD, BONNYBRIDGE, FK4 2BS, T: +44 (0)1324 812272, E: sales@ermoffat.co.uk, Web: www.ermoffat.co.uk								A4