



Moffat Specification

- TOP ----- 1.2mm Thick 304 Grade St/Steel
- TOP TURNDOWN (Front & Ends) ----- 50mm
- UPSTAND ----- 50mm High / 21mm Return to Wall / 12mm Downturn
- BOWL ----- 1.2mm Thick 304 Grade St/Steel
- BOWL FITTINGS ---- 38mm Waste With Corner Strainer or Overflow Plug & Chain
- TAP HOLES PER BOWL ----- 2x Ø25mm AT 180mm Centres
- RELIEF PATTERN DRAINER WITH ANTI-DRIP EDGE ----- Wipe Dry
- UNDERSHELF ----- 1mm Thick 430 Grade St/Steel, 43mm Turndowns
- LEGS ----- 30x30mm 430 Grade St/Steel
- Tie Bars (If Applicable) ----- 30x30/15/5mm 430 Grade St/Steel
- PANELS (If Applicable) ----- 0.7mm Thick 430 Grade St/Steel
- FEET ----- Aluminium Adjustable Floor Fixing +20mm/-15mm
c/w Earth Bonding Tab

ALL SHEET METAL DIMENSIONS ARE I/S (INSIDE SIZES) (UNLESS OTHERWISE STATED)

ALL DIMENSIONS IN (mm), TOLERANCE = LINEAR ± 0.5mm, ANGULAR ± 0.5mm (OR AS STATED). ALL SHARP EDGES TO BE REMOVED FROM SHEET METAL PARTS.

Product	FABRICATION			Product No	SSU247DBBD			© No reproduction or publication of this drawing may be made, and no article may be manufactured or assembled in accordance with this drawing without prior written consent. This prohibition is a term of any contract relating to this drawing. Rights reserved under the Copyright Act 1956 as amended by the Design Copyright Act 1968.		The Catering Equipment Company		
Description	SINK UNIT 2400x700x900mm High			Desp/Date								
Material/Finish			Thickness		Quote No.	N/A		Dwg No.	SUA-001469		Issue	
Legacy P/N			Weight		SO Number	N/A		Drawn By	J.Anderson		A	
Client					Approved By			Date	02/02/2018			
Client Project								Scale	1 : 20	Sheet	1 / 1	A4