







Morrat Specification

TOP TURNDOWN (Front & Ends) — 50mm
UPSTAND — 50mm High / 21mm Return to Wall / 12mm Downturn
BOWL — 1.2mm Thick 304 Grade St/Steel
BOWL FITTINGS — 38mm Waste With Corner Strainer or Overflow Plug & Chain
TAP HOLES PER BOWL — 2x Ø25mm AT 180mm Centres
RELIEF PATTERN DRAINER WITH ANTI-DRIP EDGE — Wipe Dry
UNDERSHELF — 1mm Thick 430 Grade St/Steel,43mm Turndowns
LEGS — 30x30/mm 430 Grade St/Steel
Tie Bars (If Applicable) — 30x30/15/5mm 430 Grade St/Steel
PANELS (If Applicable) — 0.7mm Thick 430 Grade St/Steel
FEET — Aluminium Adjustable Floor Fixing +20mm/-15mm
c/w Earth Bonding Tab

ALL SHEET METAL DIMENSIONS ARE I/S (INSIDE SIZES) (UNLESS OTHERWISE STATED)		ALL DIMENSIONS IN (IIIII), TOLERANCE = LINEAR ± 0.5IIIII, ANGULAR ± 0.5IIIII (OR AS STATED). ALL SHARP EDGES TO BE REMOVED FROM SHEET METAL PARTS.			
Product	FABRICATION	Product No	SSU765B	No reproduction or publication of this drawing may be made, and no article may be manufactured	(MOFFAT)
Description	SINK LINIT 700v650v900mm High			or assembled in accordance with this drawing without prior written consent. This prohibition is a term	

Description SINK UNIT /00x650x900mm High of any contract relating to this drawing. Rights reserved under the Copyright Act 1956 as ammended by the Design Copyright Act 1968. The Catering Equipment Company Material/Finish Thickness Desp/Date Legacy P/N Weight N/A Dwg No. SUA-001352 Quote No. Issue Client N/A N/A Drawn By L.Barr SO Number Client Project 11/01/2018 N/A Approved By Date E & R MOFFAT LTD, SEABEGS ROAD, BONNYBRIDGE, FK4 2BS, T: +44 (0)1324 812272, E: sales@ermoffat.co.uk, Web: www.ermoffat.co.uk Scale 1:20 Sheet 1/1 **A4**