



**Moffat Specification**

TOP	-----1.2mm Thick 304 Grade St/Steel
TOP TURNDOWN (Front & Ends)	----- 50mm
UPSTAND	----- 50mm High / 21mm Return to Wall / 12mm Downturn
BOWL	-----1.2mm Thick 304 Grade St/Steel
BOWL FITTINGS	---- 38mm Waste With Corner Strainer or Overflow Plug & Chain
TAP HOLES PER BOWL	----- 2x Ø25mm AT 180mm Centres
RELIEF PATTERN DRAINER WITH ANTI-DRIP EDGE	----- Wipe Dry
UNDERSHELF	----- 1mm Thick 430 Grade St/Steel, 43mm Turndowns
LEGS	----- 30x30mm 430 Grade St/Steel
Tie Bars (If Applicable)	----- 30x30/15/5mm 430 Grade St/Steel
PANELS (If Applicable)	----- 0.7mm Thick 430 Grade St/Steel
FEET	----- Aluminium Adjustable Floor Fixing +20mm/-15mm c/w Earth Bonding Tab

ALL SHEET METAL DIMENSIONS ARE I/S (INSIDE SIZES) (UNLESS OTHERWISE STATED)

ALL DIMENSIONS IN (mm), TOLERANCE = LINEAR ± 0.5mm, ANGULAR ± 0.5mm (OR AS STATED). ALL SHARP EDGES TO BE REMOVED FROM SHEET METAL PARTS.

Product	FABRICATION			Product No	SSU77B							
Description	SINK UNIT 700x700x900mm High											
Material/Finish	Thickness		Desp/Date				<small>© No reproduction or publication of this drawing may be made, and no article may be manufactured or assembled in accordance with this drawing without prior written consent. This prohibition is a term of any contract relating to this drawing. Rights reserved under the Copyright Act 1956 as amended by the Design Copyright Act 1968.</small>					
Legacy P/N	Weight		Quote No.		N/A							
Client	N/A		SO Number		N/A		Dwg No. SUA-001405					
Client Project	N/A		Approved By				Issue					
E & R MOFFAT LTD, SEABEGS ROAD, BONNYBRIDGE, FK4 2BS, T: +44 (0)1324 812272, E: sales@ermoffat.co.uk, Web: www.ermoffat.co.uk							Scale 1 : 20		Sheet 1 / 1		A4	