

Moffat Specification

Flat belt type conveyor.

Sensor limit switch at the end of the conveyor

Emergency-stop button at each end.

Speed adjustable from 0 to 12 metres/minute

Maintenance-free drum motor

Dimensions

Length - 7000mm

Depth - 550mm

Height - 900mm

Weight - 95kg

Power Supply

When supplied as a motorized belt only

the power requirements is 13amp 1PH.

Optional splash proof 13amp sockets

for auxiliary equipment can be fitted,

each optional 13 amp socket is protected by

a 13amp R.C.B.O. fitted in a splash proof M.C.B. board.

Power supply requirement is made bespoke for each site and depending on how many sockets are fitted.

Materials

1.2mm 304 Grade St/ Steel Chassis Top & Supports.



0.7mm 430 Grade St Steel Ancillary Parts.

Installation

Floor fixing adjustable for height feet.

ALL SHEET METAL DIMENSIONS ARE I/S (INSIDE SIZES) (UNLESS OTHERWISE STATED)

ALL DIMENSIONS IN (mm), TOLERANCE = LINEAR $\pm 0.5\text{mm}$, ANGULAR $\pm 0.5\text{mm}$ (OR AS STATED). ALL SHARP EDGES TO BE REMOVED FROM SHEET METAL PARTS

Product	CONVEYOR			Product No						
Description	CVB7S *** 7 METRE STATIC BELT ***							The Catering Equipment Company		
Material/Finish		Thickness		Desp/Date		Dwg No.	VCP-088025-1	Issue		
Legacy P/N		Weight	95kg	Quote No.		Drawn By	N.Raymen	-		
Client				SO Number	STANDARD	Date	16/02/2021			
Client Project				Approved By		Scale	1 : 45	Sheet	1 / 2	A4
E & R MOFFAT LTD, SEABEGS ROAD, BONNYBRIDGE, FK4 2BS, T: +44 (0)1324 812272, E: sales@ermoffat.co.uk, Web: www.ermoffat.co.uk										

No reproduction or publication of this drawing may be made, and no article may be manufactured or assembled in accordance with this drawing without prior written consent. This prohibition is a term of any contract relating to this drawing. Rights reserved under the Copyright Act 1956 as amended by the Design Copyright Act 1968.

