



**Warning**

Do not install unit in draughty conditions where the air movement is greater than 0.2mtr/sec. e.g.near entrance/exit doors, open windows, under air conditioning units or a ceiling mounted fan Ambient room conditions must not drop below 16°C . Ticket strips must be in place on each shelf and the front tray must not be removed



**Moffat Specification**

**Heated Display**  
Recirculated forced air system  
LED Illumination  
with internal adjustable shelving  
ticket strips and front tray and  
rear sliding double glazed doors

**Capacity**  
0.20 m3

**Dimensions**  
Width - 1158mm  
Depth - 660mm  
Height - 816mm  
Weight - 87kg

**Power Rating**  
2.5kw  
complete with a 2m long cord set & 13amp plug

**Materials**  
1.2mm 304 Grade St/ Steel Top & Supports  
0.7mm 430 Grade St/ Steel Internal Structure  
6mm Tempered Glass

**Installation**  
Counter Top Flush Fit Cut Out Dimensions  
1164mm x 666mm x 25mm  
Counter Support Cut Out Dimensions  
1140mm x 642mm

ALL SHEET METAL DIMENSIONS ARE I/S (INSIDE SIZES) (UNLESS OTHERWISE STATED)

ALL DIMENSIONS IN (mm), TOLERANCE = LINEAR ± 0.5mm, ANGULAR ± 0.5mm (OR AS STATED). ALL SHARP EDGES TO BE REMOVED FROM SHEET METAL PARTS

Product	GRAB & GO'S			Product No							
Description	D3GH										
Material/Finish	Thickness			Desp/Date							
Legacy P/N	Weight	87kg		Quote No.							
Client				SO Number	N/A		Dwg No.	GGP-027328			
Client Project				Approved By			Drawn By	ABB			
							Date	26/02/2019			
E & R MOFFAT LTD, SEABEGS ROAD, BONNYBRIDGE, FK4 2BS, T: +44 (0)1324 812272, E: sales@ermoffat.co.uk, Web: www.ermoffat.co.uk							Scale	1:20	Sheet	1 / 2	A4

No reproduction or publication of this drawing may be made, and no article may be manufactured or assembled in accordance with this drawing without prior written consent. This prohibition is a term of any contract relating to this drawing. Rights reserved under the Copyright Act 1956 as amended by the Design Copyright Act 1968.

