







Moffat Specification

TOP — 1.2mm Thick 304 Grade St/Steel
TOP TURNDOWN (Front & Ends) — 50mm
UPSTAND — 50mm High / 21mm Return to Wall / 12mm Downturn
BOWL — 50mm High / 21mm Return to Wall / 12mm Downturn BOWL -----1.2mm Thick 304 Grade St/Steel BOWL FITTINGS ---- 38mm Waste With Corner Strainer or Overflow Plug & Chain TAP HOLES PER BOWL ------ 2x Ø25mm AT 180mm Centres RELIEF PATTERN DRAINER WITH ANTI-DRIP EDGE ------ Wipe Dry UNDERSHELF ------ 1mm Thick 430 Grade St/Steel,43mm Turndowns ----- 30x30mm 430 Grade St/Steel -- Aluminium Adjustable Floor Fixing +20mm/-15mm c/w Earth Bonding Tab

ALL SHEET METAL DIMENSIONS ARE I/S (INSIDE SIZES) (UNLESS OTHERWISE STATED)		ALL DIMENSIONS IN (IIII	ALL DIMENSIONS IN (MIII), TOLERANCE = LINEAR ± 0.5MIIII, ANGULAR ± 0.5MIIII (OR AS STATED). ALL SHARP EDGES TO BE REMOVED FROM SHEET METAL PARTS		
Product	FABRICATION	Product No	SSU77B	No reproduction or publication of this drawing may be made, and no article may be manufactured	(MOFFAT)
Description	SINK UNIT 700x700x900mm High			or assembled in accordance with this drawing without prior written consent. This prohibition is a term of any contract relating to this drawing. Rights reserved	
Material/Finish	Thickness	Docn/Data		under the Copyright Act 1956 as ammended by the	The Catering Equipment Company

Material/Finish Desp/Date Weight N/A Dwg No. SUA-001405 Legacy P/N Quote No. Issue N/A N/A Drawn By J.Anderson SO Number Client B 01/02/2018 Client Project N/A Approved By Date E & R MOFFAT LTD, SEABEGS ROAD, BONNYBRIDGE, FK4 2BS, T: +44 (0)1324 812272, E: sales@ermoffat.co.uk, Web: www.ermoffat.co.uk 1:20 Scale Sheet 1/1 Α4