



**Moffat Specification**

TOP ----- 1.2mm Thick 304 Grade St/Steel  
 TOP TURNDOWN (Front & Ends - 4 Sides On C/Tables) ----- 50mm  
 UPSTAND (WB's Only) ---- 50mm High / 21mm Return to Wall / 12mm Downturn  
 UNDERTOP ----- 1.2mm Thick Galvanised Steel  
 UNDERSHELF (If Applicable) -- 1mm Thick 430 Grade St/Steel, 43mm Turndowns  
 LEGS ----- 30x30mm 430 Grade St/Steel  
 Tie Bars (If Applicable)----- 30x30/15/5mm 430 Grade St/Steel  
 PANELS (If Applicable) ----- 0.7mm Thick 430 Grade St/Steel  
 FEET (If Applicable) ----- Aluminium Adjustable Floor Fixing +20mm/-15mm  
 CASTORS (If Applicable) ----- Ø125 Rubber Faced Swivel - 2x Braked  
 c/w Earth Bonding Tab

ALL SHEET METAL DIMENSIONS ARE I/S (INSIDE SIZES) (UNLESS OTHERWISE STATED)

ALL DIMENSIONS IN (mm), TOLERANCE = LINEAR ± 0.5mm, ANGULAR ± 0.5mm (OR AS STATED). ALL SHARP EDGES TO BE REMOVED FROM SHEET METAL PARTS.

Product	FABRICATION			Product No	SWB965		© No reproduction or publication of this drawing may be made, and no article may be manufactured or assembled in accordance with this drawing without prior written consent. This prohibition is a term of any contract relating to this drawing. Rights reserved under the Copyright Act 1956 as amended by the Design Copyright Act 1968.			
Description	WORK BENCH 900x650x900mm High			Desp/Date						
Material/Finish		Thickness		Quote No.	N/A		Dwg No.	WBA-000234		Issue
Legacy P/N	N/A		Weight	SO Number	N/A		Drawn By	J.Anderson		<b>A</b>
Client	N/A			Approved By			Date	12/01/2018		
Client Project	N/A			Scale	1:20		Sheet	1 / 1		<b>A4</b>
E & R MOFFAT LTD, SEABEGS ROAD, BONNYBRIDGE, FK4 2BS, T: +44 (0)1324 812272, E: sales@ermoffat.co.uk, Web: www.ermoffat.co.uk										